

# Explosion Proof Wall Mount Pressurization

## W - 18 - A - 1 - 2 - B - 5 - 216 - PRESS - X - X

**Wall Mount**

### Coating Options

P - Phenicon  
H - Hersite  
B - Blygold  
K - Khemcromik  
O - Other

### 1 Ton - 7 Ton

17 = 1.5 Ton  
18 = 1.5 Ton \*\*  
24 = 2 Ton  
30 = 2.5 Ton  
36 = 3 Ton  
42 = 3.5 Ton  
48 = 4 Ton  
60 = 5 Ton  
70 = 6 Ton  
Larger Upon Request

### Case Material

1 - Steel  
2 - Stainless Steel 316  
3 - Galvanized

### Pressurization

### Volts/Phase/Hz

216 - 230/1/60  
236 - 208/3/60  
436 - 460/3/60  
215 - 220/1/50  
335 - 390/3/50  
435 - 440/3/50

A = Rt. Hand Controls  
B = Left Hand Controls

### FEATURES:

Compressor  
R-410A Refrigerant  
Standard Galvanized 20 Gauge Cabinet  
Twin Blowers  
Full Length Mounting Brackets  
Built-In Circuit Breakers  
High & Low Pressure Switches are Auto-Reset  
\*\*Low Ambient Fan Cycling Switch (except model W18)  
Aluminum Finned Copper Coils  
Phase Rotation Monitor (3-phase units only)  
Electric Heat Stripes  
Filter Service Door  
Condenser Fan & Motor Shroud  
Slope Top  
Compressor Control Module  
Liquid Line Filter Dryer  
Top Rain Flashing

2kw - 25kw  
Electric Heat kw

Class N.E.C  
1 = Class 1  
2 = Class 2

N.E.C Division  
1 = Division 1  
2 = Division 2

X = Standard "C", "D"  
Add A or B for  
Groups "A" or "B"

